

# DIGITUS 1.25 Gbps copper SFP-module, RJ45

DN-81005-01  
EAN 4016032454915



### 1.25 Gbps Copper SFP Module, RJ45, HP-compatible 10/100/1000Base-T, up to 100m, HP

The DIGITUS® Mini GBIC (SFP) transceiver modules offer the highest quality and reliability. The module offers a perfect opportunity for you to extend your Gigabit network switch with a free SFP Uplink Port around an additional RJ45 connection. Thanks to the hot-plug capability, you can install the module without any interruption to the network traffic or restart of the device. In addition, conformity with the MSA (Multi Source Agreement) standard provides compatibility with the current network switch manufacturers.

#### The plug and play extension for your network switch

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: HP
- Up to 1.25 Gbps bidirectional maximum data rate
- Compliant to IEEE 802.3z Gigabit Standard
- High quality and excellent reliability

- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable - installation possible while in operation
- Auto MDI/MDI-X
- Connection: 1x RJ45, CAT 5
- Distance: up to 100 m
- Operating temperature: 0 °C ~ 70 °C
- Manufacturer compatibility: Universal (MSA)
- Connector: RJ45
- DDM Support: no
- Distance (km): 0.1
- Mode: Copper
- Ethernet speed: Gigabit

#### Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.20	1.50	1.50	7.00	0.00

#### More images:



SFP Modules									
Product Number	MSA Code	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Version		
DN-81001	401603200001	1.0 Gbps	2 km	LC-Multifiber Duplex	25Pin	0°C to 70°C	✓		
DN-81002	401603200002	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81003	401603200003	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81004	401603200004	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81005	401603200005	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81006	401603200006	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81007	401603200007	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81008	401603200008	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81009	401603200009	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81010	401603200010	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81011	401603200011	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81012	401603200012	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81013	401603200013	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81014	401603200014	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81015	401603200015	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81016	401603200016	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81017	401603200017	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81018	401603200018	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81019	401603200019	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		
DN-81020	401603200020	1.0 Gbps	2 km	LC-Singlemode Duplex	25Pin	0°C to 70°C	✓		

