



- DESIGN: MODULAR
- DEGREE OF PROTECTION: IP66
- YEARS OF WARRANTY: 2
- UV RESISTANCE: YES
- READY TO CONNECT: YES
- WEIGHT: 34.590 KG



The connection panel from the Polish manufacturer KENO provides protection against the effects of both indirect and direct discharges on the direct current side. It is designed for use in grounded and isolated photovoltaic installations. Due to the high degree of IP protection, outdoor installation is possible. The design of the switchgear is intended for surface mounting. Depending on the equipment, switchboards can perform various functions.

BASIC PARAMETERS DC SIDE

Number of inputs PV string outputs	16 16
Quantity Type of DC surge arrester Type	16 Citel T1/T2
Connection type	Array MC4 Stäubli

ELECTRICAL AND MECHANICAL PARAMETERS OF THE HOUSING

Model	BF-IP66 84
The number of modules	84
Dimensions of housing without chokes and MC4 (Length Width Height)	300.00 500.00 700.00
Design in accordance with	EN/IEC 62208, EN/IEC 61439-1-4, Dyrektywa RoHS 2011/65/EU Dyrektywa Niskonapięciowa 2006/95/EC (do 1500 VDC)
Level of security	IP66
Protection class	II
Rated insulation voltage U_i	1000 V AC, 1500 V DC
The incandescent rod test	960°C
Impact resistance	IK10 +35°C / IK08 -25°C
UV resistance	UL 508
Flammability class	UL 94-5VA / UL 94-V0

NEMA standard	NEMA 4, 4X, 12, 13
Temperature °C (short-term)	-40 ... 120°C
Temperature °C (continuous work)	-40 ... 80°C
Temperature °F (short-term)	-40 ... 250°F
Temperature °F (continuous work)	-40 ... 175°F

DC surge arrester used (SPD)