



- DESIGN: MODULAR
- DEGREE OF PROTECTION: IP66
- YEARS OF WARRANTY: 2
- UV RESISTANCE: YES
- READY TO CONNECT: YES
- WEIGHT: 10.740 KG



BASIC PARAMETERS AC SIDE

AC Surge Protector Type	0 -
Overcurrent circuit breaker	Without miniature circuit breaker

ELECTRICAL AND MECHANICAL PARAMETERS OF THE HOUSING

Model	BF-IP66 48
The number of modules	48
Dimensions of housing without chokes and MC4 (Length Width Height)	210.00 400.00 500.00
Design in accordance with	EN/IEC 62208, EN/IEC 61439-1-4, Dyrektywa RoHS 2011/65/EU Dyrektywa Niskonapięciowa 2006/95/EC (do 1500 VDC)
Level of security	IP66
Protection class	II
Rated insulation voltage U_i	1000 V AC, 1500 V DC
The incandescent rod test	960°C
Impact resistance	IK10 +35°C / IK08 -25°C
UV resistance	UL 508
Flammability class	UL 94-5VA / UL 94-V0
NEMA standard	NEMA 4, 4X, 12, 13
Temperature °C (short-term)	-40 ... 120°C
Temperature °C (continuous work)	-40 ... 80°C

Temperature °F (short-term)

-40 ... 250°F

Temperature °F (continuous work)

-40 ... 175°F