



- DESIGN: MODULAR
- DEGREE OF PROTECTION: IP65
- YEARS OF WARRANTY: 5
- UV RESISTANCE: YES
- READY TO CONNECT: YES
- WEIGHT: 2.700 KG



The connection panel from the Polish manufacturer KENO is intended for supplying power to photovoltaic inverters., protects against the effects of short circuits and overloads, It also ensures protection against the effects on the alternating and direct current sides. The distribution board should be used in grounded and isolated photovoltaic installations. Due to the high degree of IP protection, outdoor installation is possible. The design of the switchgear is intended for surface mounting. Depending on the equipment, switchboards can perform various functions.

BASIC PARAMETERS DC SIDE

Number of inputs PV string outputs	1 1
Quantity Type of DC surge arrester Type	1 Phoenix T2
Connection type	Array MC4 Stäubli

BASIC PARAMETERS AC SIDE

AC Surge Protector Type	Phoenix T2
Overcurrent circuit breaker	Noark B16A 3F


ELECTRICAL AND MECHANICAL PARAMETERS OF THE HOUSING

Model	PHS 12 T
Number of fields	12
Dimensions of housing without chokes and MC4 (Length Width Height)	144.00 259.00 319.00
Design in accordance with	EN 60670-1, EN 62208
Level of security	IP65
Protection class	II

Rated insulation voltage U_i	400 V AC, 1500 V DC
The incandescent rod test	650°C
Impact resistance	IK08
UV resistance	YES
Recyclable plastic	bezhalogenowy
Working temperature	-25°C - +60°C


DC surge arrester used (SPD)

Manufacturer / Model	Phoenix / VAL-MS 1000DC-PV/2+V
Surge protection	T2
Idle voltage U_{OCSTC}	≤ 975 V DC
Maximum discharge current I_{max} (8/20) μs	40 kA
Response time t_A	≤ 25 ns
Total current discharged I_{total} (8/20) μs	40 kA
Insulation resistance R_{iso}	> 5 G Ω (by 500 V DC)
Nominal discharge current I_n (8/20) μs	15 kA
Rated load current I_L	80 A
Long-term operating current I_{CPV}	< 20 μA
Maximum permanent voltage U_{CPV}	1170 V DC
Short circuit resistant I_{SCPV}	2000 A
Residual voltage U_{res}	$\leq 3,7$ kV (by I_n)
-	$\leq 3,1$ kV (by 5 kA)
-	$\leq 3,5$ kV (by 10 kA)
-	≤ 4 kV (by 20 kA)
-	$\leq 4,6$ kV (by 30 kA)
-	≤ 5 kV (by 40 kA)
Current of the protective conductor I_{PE}	≤ 20 μA DC
-	≤ 250 μA AC
Protection level U_p	$\leq 3,7$ kV
Power consumption in standby mode P_C	≤ 25 mVA
Connection configuration	Configuration Y



Overcurrent circuit breaker used (MCB) (1)

Manufacturer / Model	Noark / Ex9BN 3P B16
Rated current	16A; 3-F
Rated operational voltage U_e	230/415 V AC
-	72 V DC to the pole (1P, 2P)
-	48 V DC to the pole (3P, 4P)
Minimum voltage	12 V AC/DC
Rated impulse withstand voltage U_{imp} in accordance with IEC 60898-1	6 kV
Rated impulse withstand voltage U_{imp} in accordance with IEC 60947-2	6 kV
Rated short-circuit breaking capacity I_{cn} in accordance with IEC 60898-1	6 kA
Rated short-circuit breaking capacity I_{cn} in accordance with IEC 60947-2	10 kA
Rated voltage of the insulation U_i	690 V AC
Number of poles	3
Frequency	50/60 Hz
Characteristic	B
Design in accordance with	IEC/EN 60898-1, IEC/EN 60947-2
Mechanical durability	20 000 connections
Electrical durability	10 000 connections
Energy limitation class	3
Category of use	A
Feed direction	Any (top or bottom)



Overvoltage limiter used (SPD) AC

Manufacturer / Model	Phoenix VAL-MS 230/3+1
Made in accordance with	EN 61643-11
Power system IEC	TN-S, TT
Surge protection	T2
Protective tracks	L-N, L-PE, N-PE
Direction of action	3L-N & N-PE
Rated voltage U_n	240/415 V AC (TN-S)
-	240/415 V AC (TT)
Rated frequency f_N	50 Hz (60 Hz)
The highest working voltage U_c (L-N)	275 V AC
Maximum permanent voltage U_c (L-PE)	275 V AC
The highest working voltage U_c (N-PE)	260 V AC
Rated load current I_L	80 A
Current of the protective conductor I_{PE}	$\leq 5 \mu A$
Power consumption in standby mode P_c	$\leq 360 \text{ mVA}$
Nominal discharge current I_n (8/20) μs	20 kA
Maximum discharge current I_{max} (8/20) μs	40 kA
Follow current extinguishing capability I_{fi} (N-PE)	100 A
Short circuit resistant I_{SCCR}	25 kA
Protection level U_p (L-N)	$\leq 1,35 \text{ kV}$
Protection level U_p (L-PE)	$\leq 1,6 \text{ kV}$
Protection level U_p (N-PE)	$\leq 1,5 \text{ kV}$
Residual voltage U_{res} (L-N)	$\leq 1,35 \text{ kV}$ (by I_n)
-	$\leq 1,1 \text{ kV}$ (by 10 kA)
-	$\leq 1 \text{ kV}$ (by 5 kA)
-	$\leq 0,9 \text{ kV}$ (by 3 kA)
Residual voltage U_{res} (L-PE)	$\leq 1,6 \text{ kV}$ (by I_n)
-	$\leq 1,2 \text{ kV}$ (by 10 kA)
-	$\leq 1 \text{ kV}$ (by 5 kA)
-	$\leq 0,9 \text{ kV}$ (by 3 kA)
Residual voltage U_{res} (N-PE)	$\leq 0,4 \text{ kV}$ (by I_n)
-	$\leq 0,25 \text{ kV}$ (by 10 kA)
-	$\leq 0,15 \text{ kV}$ (by 5 kA)
-	$\leq 0,1 \text{ kV}$ (by 3 kA)
TOV behavior for U_t (L-N)	335 V AC (5 s / withstand mode)

-	440 V AC (120 min / safe failure mode)
TOV behavior for U_t (N-PE)	1200 V AC (200 ms / withstand mode)
Response time t_A (L-N)	≤ 25 ns
Response time t_A (L-PE)	≤ 100 ns
Response time t_A (N-PE)	≤ 100 ns
Maximum pre-fuse in through-flow installations V	80 A (gG)
Maximum fuse value for radial installations	125 A (gG)

