

To / 致:

Company / 公司: Tongwei Co., Ltd.

Contact / 联系人: Mr. Wei Yang

Email / 邮箱: YANGW012@tongwei.com

From / 自:Company / 公司: TUV NORD (HANGZHOU)
CO., LTD. / 杭州汉德质量认
证服务有限公司Contact / 联系人: Mrs. Serena.Wu/ 邬玉婷 女
士

Email / 邮箱: sewu@tuv-nord.com

Subject: Announcement of cancellation**主题: 证书取消通知**

File No.: PVP04061/26P-001

项目号:

License holder: **Tongwei Co., Ltd.**持证人: No. 588, Middle Section Tianfu Avenue, High-Tech Zone,
Chengdu, China (Sichuan) Pilot Free Trade Zone

Certificate No.: 44 780 24 406749 - 028R15M36

证书号:

Product: Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

产品: 地面用晶体硅光伏组件

Herewith it is declared, that the above noted certificate(s) has (have) been cancelled since 2026-06-24.
特此声明, 上述证书自 2026 年 6 月 24 日起被取消。

Reasons for cancellation of certificate(s):**取消原因:**☐ License holder applied for cancellation.

持证人申请取消。

☒ New certificate(s) (no: 44 780 24 406749 - 028R15M37) has (have) been issued to replace the
cancelled one(s).新证书 (证书号: 44 780 24 406749 - 028R15M37) 签发, 取代旧证书。☐ Certificate(s) is (are) expired.

证书有效期至。

☐ Certificate(s) has (have) been suspended for one year, and the factory inspection, verification, and
rectification required to restore the certificate(s) has (have) not been completed.

证书暂停满一年, 且未完成恢复证书所需厂检、核查、整改等。

☐ Certificate(s) has (have) been suspended for one year, and the annual certificate fee has (have) not
been paid.

证书暂停满一年, 未支付证书年费。

☐ Others: _____

其他情况: _____

Please stop using the invalid certificate(s) from 2026-06-24. Meanwhile, please send back the original copies of above-mentioned certificate(s) to us.

请从 2026 年 6 月 24 日起停止使用无效证书，并将上述证书原件寄回给我司。

TÜV NORD reserved the right of final explanation about the cancellation of certificate(s). TÜV NORD will not take any responsibility for the circumstance of misusing the invalid certificate(s) by the license holder or the manufacturer.

TÜV NORD 保留对证书取消的最终解释权。TÜV NORD 对证书持有者或制造商滥用无效证书的情况不承担任何责任。



Serena.Wu / 邬玉婷

Technical Support / 技术支持

Renewable Energy / 可再生能源

TUV NORD (Hangzhou) Co., Ltd. / 杭州汉德质量认证服务有限公司

Certificate



This certifies that the company:

Tongwei Co., Ltd.

No. 588, Middle Section Tianfu Avenue,
High-Tech Zone, Chengdu,
China (Sichuan) Pilot Free Trade Zone

is authorized to provide the product(s) mentioned below with the mark as illustrated.

Manufacturer and factory(-ies): See Annex 1

Description of product(s) (details see Annex 2): **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**

Trademark: See Annex 1

Certification scheme: P12.4-VA-01 Rev. 01 / 01.26 Certification scheme type: Type 5 acc. to ISO/IEC 17067:2013

Certification fundamental(s): IEC 61215-1:2021 / EN IEC 61215-1:2021,
IEC 61215-1-1:2021 / EN IEC 61215-1-1:2021, IEC 61215-2:2021 / EN IEC 61215-2:2021,
IEC 61730-1:2023, IEC 61730-2:2023

It is certified by TÜV NORD CERT GmbH that the product(s) described above has(have) been assessed according to the certification program mentioned above and found in compliance with the requirements of above specified certification fundamental(s). This certification is based on evaluation results as documented in test report(s) referenced below and production site(s) audit results as documented in factory inspection report(s) referenced in Annex 1. This certificate is valid in conjunction with these quoted report(s).

Registration no.: 44 780 24 406749 - 028R15M37

Report no.: 492013017.043

File no.: PVP03049/26P-001

Valid from: 2026-06-24

Valid until: 2029-02-25

Essen, 2026-06-24

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Please also pay attention to the information stated overleaf.

TÜV®



Scan the QR code or
visit cis.tuev-nord.com.cn to verify
the validity of the
certificate

Annex 1

to certificate registration no. 44 780 24 406749 - 028R15M37

Manufacturer:**Tongwei Co., Ltd.**

No. 588, Middle Section Tianfu Avenue, High-Tech Zone,
Chengdu, China (Sichuan) Pilot Free Trade Zone

Trademark:**Factory 1:****Tongwei Solar (Hefei) Co., Ltd.**

No.888, Changning Road, High-tech District,
Hefei City, Anhui Province, 230088, P.R. China

Factory inspection report no.:

862010358.009

Factory 2:**Tongwei Solar (Yancheng) Co., Ltd.**

No. 88, Jiuhuashan Road, Economic Development Zone,
Yancheng City, Jiangsu Province, China

Factory inspection report no.:

862010763.003

Factory 3:**Tongwei Solar (Sichuan) Co., Ltd.**

No.888, Jilin East Road, Huai Kou Street, Jintang County, Chengdu City,
Sichuan Province

Factory inspection report no.:

862010782.003

Factory 4:**Tongwei Solar (Nantong) Co., LTD**

No. 8, Bonded 10 Road, Economic Development Zone, Nantong City,
Jiangsu Province, P. R. China

Factory inspection report no.:

862010863.003

Factory 5:**Tongwei Solar (Chengdu) Co., LTD**

No. 888, Linjiaci Road, Huangjia Subdistrict, Shuangliu District, Chengdu
City, Sichuan Province, China

Factory inspection report no.:

862010864.003

Remark: Factory inspection is mandatory to be performed annually. Please refer to factory inspection report for detailed information.

Essen, 2026-06-24

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Annex 2

to certificate registration no. 44 780 24 406749 - 028R15M37

Description of product(s):

Module types:

Double Glass PV Modules with Half-cut 7" TOPCon Mono-crystalline Silicon Solar Cells:

156 cells: TWMND-78HDxxx (xxx = 580-650, in increment of 5)
 144 cells: TWMND-72HDxxx (xxx = 535-600, in increment of 5)
 132 cells: TWMND-66HDxxx (xxx = 490-550, in increment of 5)
 120 cells: TWMND-60HDxxx (xxx = 445-500, in increment of 5)
 108 cells: TWMND-54HDxxx (xxx = 400-450, in increment of 5)
 144 cells: TWMNG-72HDxxx (xxx = 580-615, in increment of 5)
 120 cells: TWMNG-60HDxxx (xxx = 485-510, in increment of 5)
 120 cells: TWMNG-60HCxxx (xxx = 485-510, in increment of 5)
 108 cells: TWMNG-54HDxxx (xxx = 435-460, in increment of 5)
 108 cells: TWMNG-54HCxxx (xxx = 435-460, in increment of 5)
 132 cells: TWMNH-66HDxxx (xxx = 580-665, in increment of 5)
 120 cells: TWMNH-60HDxxx (xxx = 530-595, in increment of 5)
 108 cells: TWMNH-54HDxxx (xxx = 475-535, in increment of 5)
 108 cells: TWMNH-54HCxxx (xxx = 475-535, in increment of 5)
 96 cells: TWMNH-48HDxxx (xxx = 420-480, in increment of 5)
 96 cells: TWMNH-48HCxxx (xxx = 420-480, in increment of 5)
 96 cells: TWMNH-48HExxx (xxx = 425-485, in increment of 5)
 96 cells: TWMNH-48HWxxx (xxx = 425-490, in increment of 5)
 xxx indicates rated output power generated from front side under STC

Maximum system voltage:	1500V
Maximum overcurrent protection rating:	30A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕ _{Isc}):	80% ± 5% or 80%±10%, refer to CDF for details

Essen, 2026-06-24

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Annex 2

to certificate registration no. 44 780 24 406749 - 028R15M37

Module types:	Double Glass PV Modules with Half-cut 8" TOPCon Mono-crystalline Silicon Solar Cells: 144 cells: TWMNF-72HDxxx (xxx = 755-820, in increment of 5) 132 cells: TWMNF-66HDxxx (xxx = 665-755, in increment of 5) 120 cells: TWMNF-60HDxxx (xxx = 605-685, in increment of 5) 108 cells: TWMNF-54HDxxx (xxx = 545-615, in increment of 5) 110 cells: TWMNF-55HDxxx (xxx = 530-565, in increment of 5) 100 cells: TWMNF-50HDxxx (xxx = 480-510, in increment of 5) xxx indicates rated output power generated from front side under STC
Maximum system voltage:	1500V
Maximum overcurrent protection rating:	35A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕIsc):	80% ± 5%
Module types:	Double Glass PV Modules with Half-cut 7" PERC Mono-crystalline Silicon Solar Cells: 156 cells: TWMPD-78HDxxx (xxx = 570-615, in increment of 5) 144 cells: TWMPD-72HDxxx (xxx = 525-565, in increment of 5) 132 cells: TWMPD-66HDxxx (xxx = 480-520, in increment of 5) 120 cells: TWMPD-60HDxxx (xxx = 440-470, in increment of 5) 108 cells: TWMPD-54HDxxx (xxx = 395-425, in increment of 5) 144 cells: TWMPG-72HDxxx (xxx = 560-590, in increment of 5) 108 cells: TWMPG-54HDxxx (xxx = 420-440, in increment of 5) 108 cells: TWMPG-54HCxxx (xxx = 420-440, in increment of 5) 132 cells: TWMPH-66HDxxx (xxx = 575-585, in increment of 5) 120 cells: TWMPH-60HDxxx (xxx = 525-530, in increment of 5) 96 cells: TWMPH-48HDxxx (xxx = 420-425, in increment of 5) 96 cells: TWMPH-48HCxxx (xxx = 420-425, in increment of 5)

Essen, 2026-06-24

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Annex 2

to certificate registration no. 44 780 24 406749 - 028R15M37

	xxx indicates rated output power generated from front side under STC
Maximum system voltage:	1500V
Maximum overcurrent protection rating:	30A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕIsc):	70% ± 5% or 70% ± 10%, refer to CDF for details

Module types:	Double Glass PV Modules with Half-cut 8" PERC Mono-crystalline Silicon Solar Cells: 132 cells: TWMPF-66HDxxx (xxx = 635-685, in increment of 5) 120 cells: TWMPF-60HDxxx (xxx = 580-620, in increment of 5) 108 cells: TWMPF-54HDxxx (xxx = 520-560, in increment of 5) 110 cells: TWMPF-55HDxxx (xxx = 530-565, in increment of 5) 100 cells: TWMPF-50HDxxx (xxx = 480-510, in increment of 5) xxx indicates rated output power generated from front side under STC
Maximum system voltage:	1500V
Maximum overcurrent protection rating:	35A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕIsc):	70% ± 5%

Essen, 2026-06-24

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Annex 2

to certificate registration no. 44 780 24 406749 - 028R15M37

Module types:	Double Glass PV Modules with Half-cut 8" HJT Mono-crystalline Silicon Solar Cells: 132 cells: TWMHF-66HDxxx (xxx = 660-740 in increment of 5) 120 cells: TWMHF-60HDxxx (xxx = 600-670, in increment of 5) xxx indicates rated output power generated from front side under STC
Maximum system voltage:	1500V
Maximum overcurrent protection rating:	35A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (φ _{Isc}):	85% ± 5%

Module types:	Double Glass PV Modules with Half-cut 7" TBC Mono-crystalline Silicon Solar Cells: 132 cells: TWMBH-66HDxxx (xxx = 635-670, in increment of 5) 120 cells: TWMBH-60HDxxx (xxx = 580-610, in increment of 5) 108 cells: TWMBH-54HDxxx (xxx = 520-545, in increment of 5) 96 cells: TWMBH-48HDxxx (xxx = 460-485, in increment of 5) xxx indicates rated output power generated from front side under STC
Maximum system voltage:	1500V
Maximum overcurrent protection rating:	35A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5

Essen, 2026-06-24

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Annex 2

to certificate registration no. 44 780 24 406749 - 028R15M37

Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕ_{Isc}):	70% $\pm$ 5%
Module types:	Double Glass PV Modules with 1/3 cut 7" TOPCon Mono-crystalline Silicon Solar Cells: 198 cells: TWMNH-66TDxxx (xxx = 615-670, in increment of 5) 180 cells: TWMNH-60TDxxx (xxx = 560-610, in increment of 5) 162 cells: TWMNH-54TDxxx (xxx = 505-545, in increment of 5) 144 cells: TWMNH-48TDxxx (xxx = 450-485, in increment of 5) xxx indicates rated output power generated from front side under STC
Maximum system voltage:	1500V
Maximum overcurrent protection rating:	35A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T_{98}):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕ_{Isc}):	85% $\pm$ 5%

Module types:	Double Glass PV Modules with 1/4 cut 7" TOPCon Mono-crystalline Silicon Solar Cells: 264 cells: TWMNH-66QDxxx (xxx = 615-670, in increment of 5) 240 cells: TWMNH-60QDxxx (xxx = 560-610, in increment of 5) 216 cells: TWMNH-54QDxxx (xxx = 505-545, in increment of 5) 204 cells: TWMNH-51QDxxx (xxx = 475-515, in increment of 5) 192 cells: TWMNH-48QDxxx (xxx = 450-485, in increment of 5) 192 cells: TWMNH-48QExxx (xxx = 450-495, in increment of 5) 192 cells: TWMNH-48QWxxx (xxx = 450-495, in increment of 5) xxx indicates rated output power generated from front side under STC
---------------	--

Essen, 2026-06-24



Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Annex 2

to certificate registration no. 44 780 24 406749 - 028R15M37

Maximum system voltage:	1500V
Maximum overcurrent protection rating:	35A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕIsc):	85% ± 5% refer to CDF for details

Module types: **Double Glass PV Modules with 1/4 cut 8" TOPCon Mono-crystalline Silicon Solar Cells:**
 264 cells: TWMNF-66QDxxx (xxx = 700-770, in increment of 5)
 xxx indicates rated output power generated from front side under STC

Maximum system voltage:	1500V
Maximum overcurrent protection rating:	35A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕIsc):	85% ± 5% refer to CDF for details

Module types: **Double Glass PV Modules with 1/3 cut 8"HJT Mono-crystalline Silicon Solar Cells:**
 198 cells: TWMHF-66TDxxx (xxx = 720-770, in increment of 5)

Essen, 2026-06-24

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Annex 2

to certificate registration no. 44 780 24 406749 - 028R15M37

	xxx indicates rated output power generated from front side under STC
Maximum system voltage:	1500V
Maximum overcurrent protection rating:	35A
Electrical protection class:	Class II
Pollution degree:	1
98 th percentile module operating temperature (T ₉₈):	70°C
Design load (positive / negative):	3600Pa / 1600Pa, refer to CDF for details
Safety factors:	1.5
Fire safety class:	Class A or Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018), refer to CDF for details
Isc bifaciality coefficient (ϕ_{Isc}):	90% $\pm$ 5% refer to CDF for details

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) with the same file no.

Isc bifaciality coefficient (ϕ_{Isc}) = $I_{sc_{rear}}/I_{sc_{front}}$, as defined in IEC TS 60904-1-2.

The tolerance of Isc bifaciality coefficient (ϕ_{Isc}) is claimed by client.

Essen, 2026-06-24



Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de