



- DESIGN: MODULAR
- DEGREE OF PROTECTION: IP65
- YEARS OF WARRANTY: 5
- UV RESISTANCE: YES
- READY TO CONNECT: YES
- WEIGHT: 1.900 KG



The connection switchgear from Polish producer KENO is designed to power photovoltaic inverters in grounded and isolated photovoltaic installations. It realizes protection against the effects of short circuits and overloads, as well as protection against the effects of direct and indirect discharges on the AC side. Due to the high degree of IP protection, outdoor installation is possible. The design of the switchgear is intended for surface mounting. Depending on the equipment, switchboards can perform various functions.

BASIC PARAMETERS AC SIDE

AC Surge Protector | Type

Dehn | T1/T2

Overcurrent circuit breaker

Noark B10A 3F

ELECTRICAL AND MECHANICAL PARAMETERS OF THE HOUSING

Model PHS 8 T

Number of fields 8

Dimensions of housing without chokes and MC4 (Length|Width|Height) 144.00 | 259.00 | 319.00

Design in accordance with EN 60670-1, EN 62208

Level of security IP65

Protection class II

Rated insulation voltage U_i 400 V AC, 1500 V DC

The incandescent rod test 650°C

Impact resistance IK08


UV resistance YES

Recyclable plastic bezhalogenowy

Working temperature -25°C - +60°C

Overcurrent circuit breaker used (MCB) (1)

Manufacturer / Model	Noark / Ex9BN 3P B10
Rated current	10A; 3-F
Rated operational voltage U_e	230/415 V AC
-	72 V DC to the pole (1P, 2P)
-	48 V DC to the pole (3P, 4P)
Minimum voltage	12 V AC/DC
Rated impulse withstand voltage U_{imp} in accordance with IEC 60898-1	6 kV
Rated impulse withstand voltage U_{imp} in accordance with IEC 60947-2	6 kV
Rated short-circuit breaking capacity I_{cn} in accordance with IEC 60898-1	6 kA
Rated short-circuit breaking capacity I_{cn} in accordance with IEC 60947-2	10 kA
Rated voltage of the insulation U_i	690 V AC
Number of poles	3
Frequency	50/60 Hz
Characteristic	B
Design in accordance with	IEC/EN 60898-1, IEC/EN 60947-2
Mechanical durability	20 000 connections
Electrical durability	10 000 connections
Energy limitation class	3
Category of use	A
Feed direction	Any (top or bottom)



Overvoltage limiter used AC (SPD)

Manufacturer / Model	Dehn DSH TNS 255
Made in accordance with	EN 61643-11 / IEC 61643-11
Surge protection	T1 / T2
Number of fields	2
Rated voltage AC (U_n)	230 V (50 / 60 Hz)

The greatest voltage of permanent work AC (U_c)	255 V (50 / 60 Hz)
Surge current (10/350 μ s) [L1+L2+L3+N-PE] (I_{total})	25 kA
Specific energy [L1+L2+L3+N-PE] (W/R)	156.25 kJ/ Ω
Surge current (10/350 μ s) [L, N-PE] (I_{imp})	12,5 kA
Specific energy [L,N-PE] (W/R)	39,06 kJ/ Ω
Nominal discharge current (8/20 μ s) [L/N-PE] / [L1+L2+L3+NPE] (I_n)	12,5 / 25 kA
Voltage protection level [L-PE]/[N-PE] (U_p)	$\leq 1,5$ / $\leq 1,5$ kV
Follow current extinguishing capability AC (I_{fi})	25 kArms
Response time (t_A)	≤ 100 ns
Maximum fuse protection	160 A gG
Occasional surges (TOV) [L-N] (U_t) - characteristic	440 V / 120 min - durable
Working temperature range (TU)	-40°C ...
Operation / failure indicator	green / red

