



- DESIGN: MODULAR
- DEGREE OF PROTECTION: IP65
- YEARS OF WARRANTY: 5
- UV RESISTANCE: YES
- READY TO CONNECT: YES
- WEIGHT: 5.800 KG



The connection switchgear from Polish producer KENO is designed to power photovoltaic inverters in grounded and isolated photovoltaic installations. It realizes protection against the effects of short circuits and overloads, as well as protection against the effects of direct and indirect discharges on the AC side. Due to the high degree of IP protection, outdoor installation is possible. The design of the switchgear is intended for surface mounting. Depending on the equipment, switchboards can perform various functions.

BASIC PARAMETERS AC SIDE

AC Surge Protector Type	Phoenix T1/T2
Overcurrent circuit breaker	Noark B40A 3F
Residual current circuit breaker	2 x 300mA type A
FR switch disconnecter	100A

ELECTRICAL AND MECHANICAL PARAMETERS OF THE HOUSING

Model	PHS 36 T
Number of fields	36
Dimensions of housing without chokes and MC4 (Length Width Height)	120.00 128.00 201.00
Design in accordance with	EN 60670-1, EN 62208
Level of security	IP65
Protection class	II
Rated insulation voltage U_i	400 V AC, 1500 V DC
The incandescent rod test	650°C
Impact resistance	IK08
UV resistance	YES

Recyclable plastic


bezhalogenowy

Working temperature

-25°C - +60°C

Overcurrent circuit breaker used (MCB) (1)

Manufacturer / Model	Noark / Ex9BN 3P B40
Rated current	40A; 3-F
Rated operational voltage U_e	230/415 V AC
-	72 V DC to the pole (1P, 2P)
-	48 V DC to the pole (3P, 4P)
Minimum voltage	12 V AC/DC
Rated impulse withstand voltage U_{imp} in accordance with IEC 60898-1	6 kV
Rated impulse withstand voltage U_{imp} in accordance with IEC 60947-2	6 kV
Rated short-circuit breaking capacity I_{cn} in accordance with IEC 60898-1	6 kA
Rated short-circuit breaking capacity I_{cn} in accordance with IEC 60947-2	10 kA
Rated voltage of the insulation U_i	690 V AC
Number of poles	3
Frequency	50/60 Hz
Characteristic	B
Design in accordance with	IEC/EN 60898-1, IEC/EN 60947-2
Mechanical durability	20 000 connections
Electrical durability	10 000 connections
Energy limitation class	3
Category of use	A
Feed direction	Any (top or bottom)



Overvoltage limiter used AC (SPD)

Manufacturer / Model	Phoenix / VAL-MS-T1/T2 335/12.5/3+1
Made in accordance with	EN 61643-11 / IEC 61643-11

Test class IEC	I / II, T1 / T2
Type EN	T1 / T2
Power system IEC	TT, TN-S
Number of poles	4
Protective tracks	L-N, L-PE, N-PE
Direction of action	3L-N & N-PE
Rated voltage U_n	240/415 V AC (TN-S)
	240/415 V AC (TT)
Rated frequency f_N	50 Hz (60 Hz)
The highest working voltage U_c (L-N)	335 V AC
Maximum permanent voltage U_c (L-PE)	335 V AC
The highest working voltage U_c (N-PE)	264 V AC
Rated load current I_L	80 A
Current of the protective conductor I_{PE}	$\leq 5 \mu A$
Power consumption in standby mode P_C	≤ 810 mVA
Nominal discharge current I_n (8/20) μs (L-N)	12,5 kA
Nominal discharge current I_n (8/20) μs (L-PE)	12,5 kA
Nominal discharge current I_n (8/20) μs (N-PE)	50 kA
Maximum discharge current I_{max} (8/20) μs	50 kA
Testing lightning current (10/350) μs (L-N), ładunek	6,25 As
Testing lightning current (10/350) μs (L-N), Specific energy	39 kJ/ Ω
Testing lightning current (10/350) μs , (L-N) wartość szczytowa prądu I_{imp}	12,5 kA
Testing lightning current (10/350) μs (L-PE), ładunek	6,25 As
Testing lightning current (10/350) μs (L-PE), Specific energy	39 kJ/ Ω
Testing lightning current (10/350) μs , (L-PE) wartość szczytowa prądu I_{imp}	12,5 kA
Testing lightning current (10/350) μs (N-PE), ładunek	25 As
Testing lightning current (10/350) μs (N-PE), Specific energy	625 kJ/ Ω
Testing lightning current (10/350) μs , (N-PE) wartość szczytowa prądu I_{imp}	50 kA
Total current discharged I_{total} (8/20) μs	50 kA
Total current discharged I_{total} (10/350) μs	50 kA
Follow current extinguishing capability I_{fi} (N-PE)	100 A
Short circuit resistant I_{SCCR}	25 kA
Protection level U_p (L-N)	$\leq 1,2$ kV
	$\leq 1,6$ kV (30 kA - 8/20 μs)

Protection level U_p (L-PE) ≤ 2 kV

Protection level U_p (N-PE) $\leq 1,7$ kV

Residual voltage U_{res} (L-N) $\leq 1,2$ kV (by I_n)

$\leq 1,1$ kV (by 10 kA)

≤ 1 kV (by 5 kA)

$\leq 0,9$ kV (by 3 kA)

Residual voltage U_{res} (L-PE) ≤ 2 kV (by I_n)

$\leq 1,5$ kV (by 10 kA)

$\leq 1,2$ kV (by 5 kA)

$\leq 1,1$ kV (by 3 kA)

Residual voltage U_{res} (N-PE) $\leq 0,6$ kV (by I_n)

$\leq 0,5$ kV (by 10 kA)

$\leq 0,5$ kV (by 5 kA)

$\leq 0,4$ kV (by 3 kA)

TOV behavior for U_t (L-N) 415 V AC (5 s / withstand mode)

457 V AC (120 min / safe failure mode)

TOV behavior for U_t (N-PE) 1200 V AC (200 ms / withstand mode)

Response time t_A (L-N) ≤ 25 ns


Response time t_A (L-PE) ≤ 100 ns

Response time t_A (N-PE) ≤ 100 ns

Maximum pre-fuse in through-flow installations V 80 A (gG - 16 mm²)

Maximum fuse value for radial installations 160 A (gG)

Maximum discharge current I_{max} (8/20) μ s 65 kA



Switch disconnecter used

Model Ex9I125 3P 100A


Design in accordance with IEC/EN 60947-3

Rated operational voltage U_e 230/400 V AC

Frequency 50/60 Hz

Rated current I_e AC-22A 230/400 V AC 100

Number of poles	3
Category of use	AC-22A
Rated voltage of the insulation U_i	500 V
Rated impulse withstand voltage U_{imp}	6 kV
Rated short-time withstand current I_{cw} , 1s	12 x I_e
Rated short-circuit making current I_{cm} (wartość szczytowa)	2500 A
Maximum fuse protection	160 A gG
Mechanical durability	20 000 connections
Electrical durability	4 000 connections



Residual current circuit breaker used (RCD)

Manufacturer / Model	Noark / Ex9L-N 300mA
Made in accordance with	EN 61008
Number of fields	2 / 4
Characteristic	A
Rated operational voltage U_e	240/415 V AC
Rated current	40 / 63 A
Minimum voltage for the RCD function	Independence from tension
Voltage range for test button	150 — 440 V
Frequency f	50 Hz
Rated voltage of the insulation U_i	500 V
Conditional rated short-circuit current I_{nc}	6 kA
Rated residual current $I_{\Delta n}$	300mA
Tenderness	sensitive to residual sinusoidal current, rectified pulsed and smooth, high frequency (1 kHz)
Response time	immediate
Rated impulse withstand voltage U_{imp}	6 kV
Shock resistance	3000 A
Mechanical durability	20 000 connections
Electrical durability	4 000 connections
Maximum fuse protection against overload	

$I_n = 40 \text{ A}$	32 A gG
----------------------	---------

$I_n = 63 \text{ A}$	50 A gG
----------------------	---------

Maximum fuse protection against short-circuit effects	
---	--

$I_n = 40 \text{ A}$	63 A gG
----------------------	---------

$I_n = 63 \text{ A}$	63 A gG
----------------------	---------

Rated making and breaking capacity I_m I_m	
--	--

$I_n = 40 \text{ A}$	500 A
----------------------	-------

$I_n = 63 \text{ A}$	630 A
----------------------	-------

Feed direction	Any (top or bottom)
----------------	---------------------

